

DOUBLE GIRDER TROLLEY						
TRANSLATION SPEED 16 m/1'						
Capacity TON	Weight kg.	Wheels Ø mm.	Power kW	RPM: 1400/min		<i>i=1/x</i>
				Mt Nm	Rid. TP	
2	450	160	0,25	51	160	43
3,2	600	160	0,25	58	160	43
4	600	160	0,25	61	160	43
5	700	160	0,37	86	160	43
6,3	700	160	0,37	92	160	43
8	900	200	0,55	158	200	54
10	950	200	0,55	169	200	54
12,5	1200	200	0,75	223	200	54
16	1500	250	0,75	290	250	66
20	2300	250	1,1	420	315	70

DOUBLE GIRDER TROLLEY						
TRANSLATION SPEED 20 m/1'						
Capacity TON	Weight kg.	Wheels Ø mm.	Power kW	RPM: 1400/min		<i>i=1/x</i>
				Mt Nm	Rid. TP	
2	450	160	0,25	44	160	35
3,2	600	160	0,25	50	160	35
4	600	160	0,37	70	160	35
5	700	160	0,37	75	160	35
6,3	700	160	0,55	104	160	35
8	900	200	0,55	137	200	44
10	950	200	0,75	176	200	44
12,5	1200	200	0,75	196	200	44
16	1500	250	1,1	326	250	54
20	2300	250	1,5	437	315	54

These tables are indicative and not binding for the selection of reducer from customers.